



GENESIS WALL PUTTY

PRODUCT NAME	GENESIS WALL PUTTY
DESCRIPTION	Genesis Wall Putty (water based) is a ready to use filler that has an excellent whiteness, coverage and application properties. Its high-quality filling properties has made it ideal for use on all types of interior masonry surfaces. It provides a smooth base for the application of all Decorative products. Genesis Wall Putty is not recommended for exterior use.
PACK SIZE	5 Kgs / 20 Kgs
COLOR RANGE	White Only
PIGMENT	Lightfast Non-Lead Pigments
FLASH POINT	Not Applicable
COMPOSITION (NOMINAL)	Binder: Acrylic Copolymer Emulsion Solvent: Water
VOLUME SOLIDS	White 45% (nominal
DRYING TIMES	Single coat at standard film thickness Touch Dry: Dependent on temperature and humidity Re-Coat: 2-3 hours
PRACTICAL COVERAGE	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surface of average porosity 3.5-4.5m ² /Kg/coat
APPLICATION TOOLS	Putty Applicator /Trowel/Scraper
DILUTION	Ready to Use, No Dilution Required.
APPLICATION CONDITIONS	Temperature: 10-35oC Humidity: Less than 80%
CLEANING UP	Clean all equipment with water immediately after use.
SURFACE PREPARATION	
New Surface	Allow all new surfaces to dry out completely. Remove all loose or defective paint or powdery residues by thorough brushing and scraping using a stiff fiber brush. Where appropriate, the surface should be rubbed down using a suitable abrasive paper and dusted off.
FILLING	
New Surface	New or bare surfaces must be clean, dry and free from masonry salts. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper or stiff brush and dust off. Treat any area affected by mould, lichens, algae or moss with bleach. After priming new surfaces with Genesis Wall Primer, fill the surface with Genesis Wall Putty. Allow it to dry for 2-3 hours and apply second coat.

GENESIS PAINTS PVT LTD



GENESIS WALL PUTTY

	Third coat is recommended for extra smoothness. After drying scuff surface using abrasive paper and dust off. Genesis Wall Putty can also be applied directly on new unpainted surfaces
Repaint for sound surface	Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Smooth the surface with Genesis Wall Putty as described above, if required.
Repaint For Powdery, Dusty Surface, Cracks and Other Surface Defects	Repair minor defects. For large holes and cracks, use sand and cement mixture. Allow it dry. Prime the surface and then fill surface imperfections with Genesis Wall Putty as described above. Scuff the surface using an abrasive paper and dust off.
SYSTEM INFORMATION	
Powdery Surface	Genesis Wall Primer (Oil based) (1 Coat)
Normal, Sound Surfaces	No Primer Required
New Surface	Genesis Wall Primer (Water based)
Filling	Genesis Wall Putty 2-3 Coat (for best results apply third coat)
Finish	Any Genesis Masonry Top Coats 3 or more coats
SAFETY, HEALTH AND ENVIRONMENT INFORMATION	Keep container tightly closed and upright to prevent leakage when not in use. Keep out of reach of children. Do not smoke.
	Avoid contact with eyes and skin. Do not swallow. In case of contact with eyes flush immediately with large amount of clean water keeping eyelids apart and seek medical advice immediately. Remove splashes from skin, use soap and water or a recognized skin cleaner
	Avoid contact with skin, it may cause sensitization. Repeated exposure may cause skin dryness or cracking If inhalation causes physical discomfort, move to fresh air
	Do not use empty container for food storage. Protect the product from extreme temperature.
	Care must be taken when transporting. Protect from extremes of temperature. Store in a cool dry place. In the event of an accident contain and collect spillage using sand or soil. Don't empty into drains or water courses. Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.
	Do not use empty container for food storage. Protect the product from extreme temperature.
	<i>CONTAINS NO ADDED LEAD, CHROME OR MERCURY.</i>